

ARJ-KL43700 (30W, 700mA, PFC)

1) Compliances and Approvals			
Approval markings	CE, F-mark, SELV		
Construction Classification	Independent		
Application	Class II, Indoor		
RoHS/REACH	ROHS, REACH		
2) Technical data for installation			
Rated mains voltage		Min. 220-240	Vrms
Operational mains voltage limits	198	264	Vrms
Mains frequency for Safety	45	50-60	Hz
Maximum driver per MCB		28	Pcs
operational mains temperature limits	-15	45	°C
DC voltage operation			
3) Performance			
Performance standard	IEC 62384:2006, GB24825-2009	Min. 28	Nom. 43 Vrms
Output Voltage		0.7 A	
Output Current		95%	105%
Output Current Tolerance			N.A
Output Voltage Tolerance			10%
Percent of the output current ripple			89%
System Efficiency			0.95
Powerfactor			10%
THD			0.5W
Input Power@ None Load			
Protection	OVP, OCP, SCP		
Thermal protection		110 degree	
Turn-on delay time		0.5 s	
4) Immunity & EMI			
EMI & Immunity	EN55015, EN61547		
- surge		LN 1.2kV test	
5) Robustness			
Withstand voltage		>3.75kV	
- Input-output		NA	
- Input-FG			
Failure rate	0.25%/ 1000Hrs	<0.1%@1000h	
Maximum Tcase	TBD		70
Life by T case Life	10% failures @ 30,000 @ Tc 70Deg@ full load	30000h <10% fail rate@Tc	
6) Mechanical			
Connection	Type 500		
Housing			
Housing material	PC		
Weight	TBD		

