



1) Compliances and Approvals

Approval markings	CE, F-mark, SELV
Construction Classification	Independent
Application	ClassII, Indoor
RoHS/REACH	ROHS, REACH

2) Technical data for installation

	Min.	Nom.	Max.	
Rated mains voltage		220-240		Vrms
Operational mains voltage limits	198		264	Vrms
Mains frequency for Safety	45	50-60	66	Hz
Maximum driver per MCB			28	Pcs
operational mains temperature limits	-15		45	°C
DC voltage operation				

3) Performance

	IEC 62384:2006, GB24825-2009	Min.	Nom.	Max.	
Output Voltage		14	40		Vrms
Output Current			0.5		A
Output Current Tolerance		95%		105%	
Output Voltage Tolerance				N.A	
Percent of the output current ripple				10%	
System Efficiency				88%	
Powerfactor				0.5	
THD				NA	
Input Power@ None Load				0.5W	
Protection	OVP, OCP, SCP				
Thermal protection				110 degree	
Turn-on delay time				0.5	s

4) Immunity & EMI

EMI & Imunity	EN55015、EN61547	
- surge		LN 1.2kV test

5) Robustness

Withstand voltage			
- Input-output		>3.75kV	
- Input-FG		NA	
Failure rate	0.25% / 1000Hrs		<0.1% @ 1000h
Maximum Tcase			80
Life by T case Life	10% failures @ 30,000 @ Tc 80Deg @ full load	30000h	<10% fail rate @ Tc

6) Mechanical

Connection	Type 500		
Housing		L	W
Housing material	PC	122.8	45
Weight	TBD	19	117.8