




LED STRIP SPECIFICATION

840 LEDs/m RGBW Flexible CSP Strip



840 LEDs/m RGBW Flexible CSP Strip



Part Number: LED840-CSP-RGBW-24V-20W-IP20 → IP20/IP65CS







Description

24V, RGBW flexible COB strip (Step length: 24V=33.3mm), with 3M adhesive tape on the back for easy installed. RGBW color, 180° beam angle.



Dimensions & Waterproof



Product Specification


Dimension	5000x12x2mm
Chip Type	CSP
Chips/m	840pcs
Step LEDs	28pcs
Step Length	33.3mm

Voltage(V)	DC24V
Power(W/m)	20W
CRI	>90
Beam Angle	180°
Operation Temperature	-20°C~50°C


Product Photometrics (Data base on IP20 CRI>90)

Color	Peak Wavelength (nm)	Dominant Wavelength (nm)	Lumen (lm/m)	Power (w/m)	Efficacy (lm/w)
Red	628.5	620.3	130	5	26
Green	518.0	523.7	300	5	60
Blue	462.9	467.1	70	5	14
2700K	/	/	400	5	80
RGB+2700K	/	/	860	20	43

Bining



Graphic Description:




For all your order

Today and tomorrow

IP20: bare, max. light output and the best color consistency, indoor use.
IP65: Silicon tube / Heat shrink tube / Extrusion tube / U milky tube + clear cover, ~3% less output and 2nd best color consistency, Indoor use or semi-outdoor use, for raining environments.

Packing Information (Data base on IP20)



Precautions for use

1. To protect the LED light strip, do not hit the light-emitting area with hard things.
2. After unpacking, please use in 24H to avoid the oxidation effect of solder joints.
3. Avoid direct contact with high temperature objects in the light-emitting area of the lamp, and the instantaneous contact temperature of the surface of the light-emitting area should be less than 210 °C.
4. The soldering iron temperature should be less than 300° during soldering, and the soldering time of single solder should be controlled within 3s.
5. It is strictly forbidden to twist the lamp with short distance. The single lamp strip (0.5 m) has a maximum twist angle of 720°.



6. The bend diameter at any position needs to be greater than 1cm.

