


# ARV-KL12015 (12V, 1.25A, 15W)



Approval markings	CE, F-mark, SELV,
Construction Classification	Independent
Application	ClassII, Indoor
RoHS/REACH	ROHS

## 2) Technical data for installation

	Min.	Nom.	Max.	
Rated mains voltage		220-240		Vrms
Operational mains voltage limits	198		264	Vrms
Mains frequency for Safety	45	50-60	66	Hz
Maximum driver per MCB			28	Pcs
operational mains temperature limits	-15		45	°C
DC voltage operation				

## 3) Performance

Performance standard	IEC 62384:2006, GB24825-2009	Min.	Nom.	Max.	
Output Voltage		12			Vrms
Ouput Current			1.25		A
Output Current Tolerance			N.A		
Output Voltage Tolerance	95%		105%		
Percent of the output current ripple			10%		
System Efficiency		83%			
Powerfactor		0.5C			
THD		NA			
Input Power@ None Load			0.5W		
Protection	OVP、OCP、SCP				
Thermal protection			110 degree		
Turn-on delay time			0.5		s

## 4) Immunity & EMI

EMI & Immunity	EN55015、EN61547			
- surge			LN 0.5kV test	

## 5) Robustness

Withstand voltage	>3.75kV			
- Input-output	NA			
	0.25%/ 1000Hrs	<0.1%@1000h		
			80	°C

Life by T case Life 10% failures @ 30,000 @ Tc 80Deg@ full 30000h <10% fail rate@Tc

## 6) Mechanical

Connection	L	W	H	M1
Housing	123	45	19	118
Housing material	PC			
Weight	TBD		g	